

Thru Hole Receptacle - Shielded



- Wiper-on-wiper contact for reliable repetitive plugging
- SMT compatible
- PCT insulator material
- Screw lockdown for reliable PCB retention
- Interface latch design for connection stability
- IEEE 1284C Interface as a 36 contact connector
- **UL 94V-0**
- Contacts: 20, 26, 36, 50 and 68 way

3M

NEW

411676

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
20	10220-6212PL	929-2837	250.00	222.00	208.00	200.00
26	10226-6212PL	929-2845	260.00	231.00	216.00	208.00
36	10236-6212PL	929-2853	295.00	262.00	246.00	236.00
50	10250-6212PL	929-2861	302.00	269.00	252.00	242.00
68	10268-6212PL	929-2870	385.00	342.00	321.00	308.00

Plastic Junction Shell



- Durable two-piece glass reinforced polyester backshell with ground strap
- Round straight exit
- Reliable metal strain relief clamp provides grounding for cable shield
- Quick release latching mechanism or screw release
- Positions: 20, 26, 36, 50

3M

NEW

411673

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
Quick release						
20	10320-52F0-008	929-2926	338.00	301.00	283.00	--
26	10326-52F0-008	929-2934	373.00	332.00	311.00	--
36	10336-52F0-008	929-2942	378.00	336.00	315.00	--
50	10350-52F0-008	929-2950	382.00	340.00	319.00	--
Screw release						
20	10320-52A0-008	929-2888	281.00	250.00	235.00	--
26	10326-52A0-008	929-2896	315.00	281.00	263.00	--
36	10336-52A0-008	929-2900	318.00	283.00	265.00	--
50	10350-52A0-008	929-2918	324.00	289.00	271.00	--

Metal Junction Shell



- Metal junction shell for round cable
- Rugged two-piece die cast metal shell with round straight exit
- Reliable metal strain relief clamp provides grounding for cable shield
- Excellent EMI/ESD protection
- Quick release latching mechanism
- 1.27mm (0.050") nickel plated aluminum casing

3M

NEW

411672

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
20	10320-A200-00	929-3019	734.00	682.00	643.00	--
26	10326-A200-00	929-3027	744.00	693.00	655.00	--
36	10336-A200-00	929-3043	765.00	705.00	671.00	--
50	10350-A200-00	929-3051	931.00	860.00	823.00	--
68	10368-A200-00	929-3060	1,010.00	931.00	886.00	--

60° Metal Junction Shell



- 60° metal junction shell for round cable
- Rugged two-piece die cast metal shell with 60° round exit
- Reliable metal strain relief clamp provides grounding for cable shield
- Excellent EMI/ESD protection
- Quick release latching mechanism
- 1.27mm (0.050") nickel plated aluminum casing
- Positions: 26, 36 and 50

3M

NEW

411670

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
26	10326-A500-00	929-3078	744.00	685.00	646.00	--
36	10336-A500-00	929-3086	752.00	691.00	651.00	--
50	10350-A500-00	929-3094	938.00	861.00	812.00	--

Plastic Shielded Junction Shell



- Durable one piece plastic over two piece metal junction shell for straight round cable
- Reliable metal strain relief clamp provides grounding for cable shield
- MDR digital LCD Interface as a 20 or 26 contact connector
- Quick release latching mechanism
- 1.27mm (0.050") nickel plated aluminum casing

3M

NEW

411674

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
20	10320-3210-000	929-2969	253.00	236.00	223.00	--
26	10326-3210-000	929-2977	256.00	241.00	231.00	--
36	10336-3210-000	929-2985	306.00	279.00	273.00	--
50	10350-3210-000	929-2993	326.00	301.00	289.00	--
68	10368-3210-000	929-3000	335.00	308.00	296.00	--

Accessories - Screw Lock

- I/O Mounting hardware for MDR
- Thread size: M2.5
- Use 2 screw locks per connector

411602

Mfrs. List No.	Order Code	Price Each			
		1+	10+	50+	100+
3341-31	929-3108	153.00	142.00	136.00	135.00

IDC 0.1" Cable Pitch

Single Row IDC Sockets and Headers

ELCO



Socket Straight PCB Pins: H=9.55, D=5.5 90° PCB Pins: H=5.5, D=9.55

- Single row 2.54mm pitch
- Mass termination
- Cable notching eliminated
- Suitable for 26/28AWG stranded ribbon cable

208866

No. of Ways	Mfrs. List No.	Order Code	Price Each			
			1+	50+	100+	500+
Socket						
8	208284008000030	636-502	100.00	95.00	88.00	71.00
14	208284014000030	636-514	105.00	99.00	93.00	73.00
18	208284018000030	636-538	124.00	119.00	111.00	87.00
24	208284024000030	636-551	135.00	131.00	120.00	95.00
Straight PCB Pins						
8	108284008000030	636-563	75.00	71.00	67.00	52.00
14	108284014000030	636-575	82.00	78.00	73.00	57.00
18	108284018000030	636-599	98.00	92.00	86.00	69.00
24	108284024000030	636-629	120.00	112.00	107.00	85.00
90° PCB Pins						
8	108284008002030	636-630	75.00	71.00	67.00	52.00
14	108284014002030	636-642	82.00	78.00	73.00	59.00
18	108284018002030	636-666	98.00	93.00	88.00	69.00
24	108284024002030	636-680	120.00	114.00	107.00	84.00

Compliant Non-compliant Limited stock - RoHS replacement available