

FUS336					
Rating	Mfrs. List No.	Order Code	1+	10+	25+
15A	BLN15	303-1822			

## High Performance Fast Acting – 10.3 38mm KLK Series – Suitable For Multimeters



- For high ac fault current circuitry
- UL recognised (to 3A)
- CSA approved

Voltage rating 600V ac  
Breaking capacity 100,000A @ 600V ac

FUS335					
Rating	Mfrs. List No.	Order Code	1+	10+	25+
1A	KLK01	.302-9335			
2A	KLK02	.302-9347			
3A	KLK03	.302-9359			
4A	KLK04	.302-9360			
5A	KLK05	.302-9372			
10A	KLK10	.302-9384			
15A	KLK15	.302-9396			
20A	KLK20	.302-9402			
30A	KLK30	.302-9414			

## High Performance Fast Acting – 10.38 38 KTK Series Suitable for Multimeters



- For high ac fault current circuitry
- UL listed
- CSA certified



Voltage rating 600V Breaking capacity 100,000A @ 600V

FUS424					
Rating	Mfrs. List No.	Order Code	1+	10+	25+
0.1A	KTK-1/10	348-2789			
0.2A	KTK-2/10	348-2790			
0.25A	KTK-1/4	348-2807			
0.5A	KTK-1/2	348-2819			
1A	KTK-1	348-2820			
1.5A	KTK-1-1/2	348-2832			
2A	KTK-2	348-2844			
3A	KTK-3	348-2856			
4A	KTK-4	348-2868			
5A	KTK-5	348-2870			
6A	KTK-6	348-2881			
7A	KTK-7	348-2893			
8A	KTK-8	348-2900			
9A	KTK-9	348-2911			

## High Performance Quick Blow (F) — 10.3 x 38mm KTK-R Series



High performance, fast acting, single-element ceramic fuses for protection of branch circuits, motor control circuits, lighting ballasts and control transformers. A grooved ferrule permits mounting in rejection-type as well as standard fuseholders. UL and CSA approved.

Voltage rating 600V ac Breaking capacity 200,000A ac Mfrs. List No. KTK-R + Rating

FUS214X					
Rating	Order Code	1+	10+	50+	100+
1A	218-923				
2A	218-935				
4A	218-947				
5A	218-959				
10A	218-960				
15A	218-972				
20A	218-984				
30A	218-996				

## 10 x 38mm (1/2") HRC Cartridge Fuses and Accessories

### gR Ultra Rapid Semiconductor Fuses



- European style industrial ceramic ultra rapid fuses for protection of thyristors, diodes etc.
- UL Recognised

Rating 600Vac

Current Rating	Voltage Power Dissipation (W)	Pre-arcing I <sup>2</sup> t	Total I <sup>2</sup> t @ 600V	Order Code
4A	-	-	-	607-745
6A	1.8	6	18	607-757
10A	1.7	9	28	607-769
16A	4.8	36	120	607-770
20A	5.8	60	200	607-782
25A	6.8	120	420	607-794
30A	7.8	195	650	607-800

Mfrs. List No. 60-033-05 + Rating

FUS191X

FUS191X					
Rating	Order Code	1+	10+	100+	200+
4A	.607-745				
6A	.607-757				
10A	.607-769				
16A	.607-770				
20A	.607-782				
25A	.607-794				
30A	.607-800				

### gL (General Line)

### GOULD



European style industrial HRC ceramic fuses manufactured in accordance with IEC269-2, NFC63-210 and UNE21-103. Suitable for cable protection and applications where there are no surges to be absorbed.

Voltage rating 500V ac (32A 499493 = 400V) Breaking capacity 120,000

FUS233X

FUS233X						
Order Multiple=5	Rating	Order Code	5+	25+	100+	250+
	2A	.248-708				
	4A	.248-710				
	6A	.248-721				
	10A	.248-733				
	16A	.248-745				
	20A	.499-470				
	25A	.499-481				
	32A	.499-493				

### aM (Motor Rated)

### GOULD




European style industrial HRC ceramic fuses manufactured in accordance with IEC269-2, NFC63-210 and UNE21-103. Suitable for applications where an initial surge has to be absorbed (i.e. motor starts).

Voltage rating 500V ac (248-691 = 400V ac) Breaking capacity 120,000A

FUS232X

FUS232X						
Order Multiple=5	Rating	Order Code	5+	25+	100+	250+
	2A	.248-630				
	4A	.248-642				
	6A	.248-654				
	10A	.248-666				
	16A	.248-678				
	20A	.248-680				
	25A	.248-691				

### Fuse Clips



PCB mounting bright tinned spring bronze fuse clips suitable for all 1/2" (10.38mm) cartridge fuses.

Rating 20A (dependent on track size of PCB) Mfrs. List No. 1A3400-09

FUS215

FUS215			
2 Per Pack	Order Code	1+	Price Per Pack
	219-083	5+	25+ 50+

Continued